

000000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

SECTION 1. IDENTIFICATION

Product name : Solstice® 449A (R-449A)

Number : 000000023760

Product Use Description : Refrigerant

Manufacturer or supplier's details : Honeywell International Inc.
115 Tabor Road
Morris Plains, NJ 07950-2546

For more information call : 800-522-8001
+1-973-455-6300

(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414
: **Transportation (CHEMTREC): 1-800-424-9300 or +1-703-527-3887**
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : Liquefied gas

Color : clear colourless

Odor : slight ether-like

00000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

Classification of the substance or mixture

Classification of the substance or mixture : Gases under pressure, Liquefied gas
Simple Asphyxiant

GHS Label elements, including precautionary statements

Symbol(s) :



Signal word : Warning

Hazard statements : Contains gas under pressure; may explode if heated.
May displace oxygen and cause rapid suffocation.

Precautionary statements : **Storage:**
Protect from sunlight. Store in a well-ventilated place.

Hazards not otherwise classified : May cause frostbite.
Excessive exposure may cause central nervous system effects including drowsiness and dizziness. Excessive exposure may also cause cardiac arrhythmia.
May cause eye and skin irritation.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture

Chemical name	CAS-No.	Concentration
---------------	---------	---------------

000000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

1,1,1,2-Tetrafluoroethane	811-97-2	25.70 %
2,3,3,3-Tetrafluoroprop-1-ene	754-12-1	25.30 %
Pentafluoroethane	354-33-6	24.70 %
Difluoromethane	75-10-5	24.30 %

SECTION 4. FIRST AID MEASURES

- General advice : First aider needs to protect himself. Move out of dangerous area. Take off all contaminated clothing immediately.
- Inhalation : Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-ephedrine group.
- Skin contact : After contact with skin, wash immediately with plenty of water. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a physician.
- Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.
- Ingestion : Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. Call a physician immediately.

Notes to physician

- Indication of immediate medical attention and special treatment needed, if : Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life

00000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

necessary

support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-bitten areas as needed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : The product is not flammable.
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Specific hazards during firefighting : Contents under pressure.
This product is not flammable at ambient temperatures and atmospheric pressure.
However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.
Container may rupture on heating.
Cool closed containers exposed to fire with water spray.
Do not allow run-off from fire fighting to enter drains or water courses.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Fire may cause evolution of:
Halogenated compounds
Hydrogen fluoride
Carbon oxides
Carbonyl halides
- Special protective equipment for firefighters : In the event of fire and/or explosion do not breathe fumes.
Wear self-contained breathing apparatus and protective suit.
No unprotected exposed skin areas.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Wear personal protective equipment. Unprotected persons

000000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

must be kept away.
Remove all sources of ignition.
Avoid skin contact with leaking liquid (danger of frostbite).
Ventilate the area.
After release, disperses into the air.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Avoid accumulation of vapours in low areas.
Unprotected personnel should not return until air has been tested and determined safe.
Ensure that the oxygen content is $\geq 19.5\%$.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
The product evaporates readily.

Methods and materials for containment and cleaning up : Ventilate the area.

SECTION 7. HANDLING AND STORAGE**Handling**

Precautions for safe handling : Handle with care.
Avoid inhalation of vapour or mist.
Do not get in eyes, on skin, or on clothing.
Wear personal protective equipment.
Use only in well-ventilated areas.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Follow all standard safety precautions for handling and use of compressed gas cylinders.
Use authorized cylinders only.
Protect cylinders from physical damage.
Do not puncture or drop cylinders, expose them to open flame or excessive heat.
Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
Do not remove screw cap until immediately ready for use.
Always replace cap after use.

Advice on protection against fire and explosion : The product is not flammable.
Can form a combustible mixture with air at pressures above

00000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

atmospheric pressure.

Storage

Conditions for safe storage, including any incompatibilities : Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Keep containers tightly closed in a dry, cool and well-ventilated place.
Storage rooms must be properly ventilated.
Ensure adequate ventilation, especially in confined areas.
Protect cylinders from physical damage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Do not breathe vapour.
Avoid contact with skin, eyes and clothing.
Ensure that eyewash stations and safety showers are close to the workstation location.

Engineering measures : General room ventilation is adequate for storage and handling.
Perform filling operations only at stations with exhaust ventilation facilities.

Eye protection : Wear as appropriate:
Safety glasses with side-shields
If splashes are likely to occur, wear:
Goggles or face shield, giving complete protection to eyes

Hand protection : Leather gloves
In case of contact through splashing:
Protective gloves
Neoprene gloves
Polyvinyl alcohol or nitrile- butyl-rubber gloves

Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).
Wear cold insulating gloves/ face shield/ eye protection.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

000000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

Wear a positive-pressure supplied-air respirator.
 Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
 For rescue and maintenance work in storage tanks use self-contained breathing apparatus.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
 Ensure adequate ventilation, especially in confined areas.
 Avoid contact with skin, eyes and clothing.
 Remove and wash contaminated clothing before re-use.
 Keep working clothes separately.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis
1,1,1,2-Tetrafluoroethane	811-97-2	TWA : Time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
1,1,1,2-Tetrafluoroethane	811-97-2	TWA : Time weighted average	4,240 mg/m3 (1,000 ppm)	2007	WEEL:US. OARS. WEELs Workplace Environmental Exposure Level Guide
2,3,3,3-Tetrafluoroprop-1-ene	754-12-1	TWA : Time weighted average	(500 ppm)	2009	WEEL:US. OARS. WEELs Workplace Environmental Exposure Level Guide
2,3,3,3-Tetrafluoroprop-1-ene	754-12-1	TWA : Time weighted average	(500 ppm)	03 15 2010	Honeywell:Limit established by Honeywell International Inc.

SAFETY DATA SHEET

Honeywell**000000023760**

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

2,3,3,3-Tetrafluoroprop-1-ene	754-12-1	STEL : Short term exposure limit	(1,500 ppm)	03 15 2010	Honeywell:Limit established by Honeywell International Inc.
Pentafluoroethane	354-33-6	TWA : Time weighted average	4,900 mg/m3 (1,000 ppm)	2007	WEEL:US. OARS. WEELs Workplace Environmental Exposure Level Guide
Pentafluoroethane	354-33-6	TWA : Time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
Difluoromethane	75-10-5	TWA : Time weighted average	2,200 mg/m3 (1,000 ppm)	2007	WEEL:US. OARS. WEELs Workplace Environmental Exposure Level Guide
Difluoromethane	75-10-5	TWA : Time weighted average	(1,000 ppm)	1994	Honeywell:Limit established by Honeywell International Inc.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquefied gas

Color : clear colourless

Odor : slight ether-like

Odor threshold : Note: no data available

00000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

pH	: Note: neutral
Melting point/range	: Note: no data available
Boiling point/boiling range	: Note: no data available
Flash point	: Note: Not applicable
Evaporation rate	: Note: no data available
Lower explosion limit	: Note: None
Upper explosion limit	: Note: None
Vapor pressure	: 1,142 kPa at 21.1 °C(70.0 °F)
Vapor density	: Note: no data available, (Air = 1.0)
Density	: 1.11 g/cm ³
Water solubility	: Note: no data available
Partition coefficient: n-octanol/water	: Note: no data available
Ignition temperature	: Note: no data available
Decomposition temperature	: > 250 °C Note: To avoid thermal decomposition, do not overheat.
Viscosity, dynamic	: Note: no data available

000000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

Viscosity, kinematic : Note: no data available

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Hazardous polymerisation does not occur.

Conditions to avoid : Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Decomposes under high temperature.
Some risk may be expected of corrosive and toxic decomposition products.
Can form a combustible mixture with air at pressures above atmospheric pressure.
Do not mix with oxygen or air above atmospheric pressure.

Incompatible materials : Potassium
Calcium
Powdered metals
Finely divided aluminium
Finely divided magnesium
Zinc

Hazardous decomposition products : Halogenated compounds
Hydrogen fluoride
Carbonyl halides
Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity
1,1,1,2-Tetrafluoroethane : LC50: > 500000 ppm

00000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

	Exposure time: 4 h Species: Rat
2,3,3,3-Tetrafluoroprop-1-ene	: LC50: > 400000 ppm Exposure time: 4 h Species: Rat Method: OECD Test Guideline 403
Pentafluoroethane	: > 769000 ppm Exposure time: 4 h Species: Rat
Difluoromethane	: LC50: > 520000 ppm Exposure time: 4 h Species: Rat
Skin irritation 2,3,3,3-Tetrafluoroprop-1-ene	: Note: Not applicable study technically not feasible
Eye irritation 2,3,3,3-Tetrafluoroprop-1-ene	: Note: Not applicable study technically not feasible
Sensitisation 1,1,1,2-Tetrafluoroethane	: Cardiac sensitization Species: dogs Note: No-observed-effect level 50 000 ppm Lowest observed effect level 75 000 ppm
2,3,3,3-Tetrafluoroprop-1-ene	: Dermal Note: Not applicable, as this product is a gas. study technically not feasible
Pentafluoroethane	: Cardiac sensitization Species: dogs Note: No-observed-effect level 75 000 ppm Lowest observed effect level

00000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

100 000 ppm

Difluoromethane : Cardiac sensitization
Species: dogs
Note: No-observed-effect level
>350 000 ppm

Repeated dose toxicity
1,1,1,2-Tetrafluoroethane : Species: Rat
NOEL: 40000 ppm

2,3,3,3-Tetrafluoroprop-1-ene : Species: Rat
Application Route: Inhalation
Exposure time: (2 Weeks)
No-observed-effect level: 50000 ppm
Method: OECD Test Guideline 412

Species: Rat
Application Route: Inhalation
Exposure time: (4 Weeks)
NOAEL (No observed adverse effect level): 50000 ppm
Method: OECD Test Guideline 412

Species: Rat
Application Route: Inhalation
Exposure time: (13 Weeks)
NOAEL (No observed adverse effect level): 50000 ppm
Method: OECD Test Guideline 413

Species: Rabbit, male
Application Route: Inhalation
Exposure time: (28 d)
No-observed-effect level: 500 ppm
Method: OECD Test Guideline 412
There are no observed toxicological effects, which result in classification as a specific target organ toxicant.

Species: Rabbit, female
Application Route: Inhalation
Exposure time: (28 d)
No-observed-effect level: 1000 ppm
Method: OECD Test Guideline 412

00000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

There are no observed toxicological effects, which result in classification as a specific target organ toxicant.

Species: Mini-pig
Application Route: Inhalation
Exposure time: (28 d)
NOAEL (No observed adverse effect level): 10000 ppm
highest exposure tested

Pentafluoroethane : Species: Rat
Application Route: Inhalation
Exposure time: (4 Weeks)
NOEL: 50000 ppm
Subchronic toxicity

Difluoromethane : Species: Rat
Application Route: Inhalation
Exposure time: (90 d)
NOEL: 50000 ppm
Subchronic toxicity

Genotoxicity in vitro
1,1,1,2-Tetrafluoroethane : Note: In vitro tests did not show mutagenic effects

2,3,3,3-Tetrafluoroprop-1-ene : Test Method: Ames test
Result: 20% and higher, positive in TA 100 and e. coli WP2 uvrA, negative in TA98, TA100, and TA1535.
Method: OECD Test Guideline 471

Pentafluoroethane : Test Method: Ames test
Result: negative

Difluoromethane : Test Method: Ames test
Result: negative

: Test Method: Chromosome aberration test in vitro
Cell type: Human lymphocytes
Result: negative
Method: OECD Test Guideline 473
Note: Dose 760,000 ppm

: Cell type: Human lymphocytes

000000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

Result: negative

: Cell type: Chinese Hamster Ovary Cells

Result: negative

: Cell type: Human lymphocytes

Result: negative

Method: Mutagenicity (in vitro mammalian cytogenetic test)

: Test Method: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo

2,3,3,3-Tetrafluoroprop-1-ene

: Species: Mouse

Cell type: Micronucleus

Dose: up to 200,000 ppm (4 hour)

Method: OECD Test Guideline 474

Result: negative

: Test Method: Unscheduled DNA synthesis

Dose: up to 50,000 ppm (4 weeks)

Method: OECD Test Guideline 486

Result: negative

: Species: Rat

Cell type: Micronucleus

Dose: up to 50,000 ppm (4 weeks)

Method: OECD Test Guideline 474

Result: negative

Difluoromethane

: Species: Mouse

Cell type: Bone marrow

Method: Mutagenicity (micronucleus test)

Result: negative

Carcinogenicity

2,3,3,3-Tetrafluoroprop-1-ene

: Species: Rat

Note: Not classified as a human carcinogen. Substance not expected to be a carcinogen based on available data.

000000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

Teratogenicity

Pentafluoroethane

: Species: Rabbit
Application Route: Inhalation exposure
NOAEL, Teratog: 50,000 ppm
NOAEL, Maternal: 50,000 ppm
Note: Did not show teratogenic effects in animal experiments.

Species: Rat
Application Route: Inhalation exposure
NOAEL, Teratog: 50,000 ppm
NOAEL, Maternal: 50,000 ppm
Note: Did not show teratogenic effects in animal experiments.

Difluoromethane

: Species: Rat
Dose: NOEL - 50,000 ppm
Note: Did not show teratogenic effects in animal experiments.

Species: Rabbit
Dose: NOEL - 50,000 ppm
Note: Did not show teratogenic effects in animal experiments.

Further information

1,1,1,2-Tetrafluoroethane

: Note:
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Rapid evaporation of the liquid may cause frostbite.
Avoid skin contact with leaking liquid (danger of frostbite).

SECTION 12. ECOLOGICAL INFORMATION

Toxicity to fish

2,3,3,3-Tetrafluoroprop-1-ene

: LC50: > 197 mg/l
Exposure time: 96 h
Species: Cyprinus carpio (Carp)
Method: OECD Test Guideline 203
Note: No demonstrable toxic effect in saturated solution.

000000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

Toxicity to daphnia and other aquatic invertebrates

2,3,3,3-Tetrafluoroprop-1-ene : EC50: > 83 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 202

Toxicity to algae

2,3,3,3-Tetrafluoroprop-1-ene : EC50: > 100 mg/l
Species: Scenedesmus capricornutum (fresh water algae)
Method: OECD Test Guideline 201

Bioaccumulation

2,3,3,3-Tetrafluoroprop-1-ene : Note: Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

Biodegradability

2,3,3,3-Tetrafluoroprop-1-ene : Result: Not readily biodegradable.
Method: OECD Test Guideline 301F

Pentafluoroethane

: Result: Not readily biodegradable.
Value: 5 %
Method: OECD 301 D

Difluoromethane

: Note: Minimal

Further information on ecology

Additional ecological information

1,1,1,2-Tetrafluoroethane : Accumulation in aquatic organisms is unlikely.
This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere.
To comply with provisions of the U.S. Clean Air Act, any residual must be recovered.

SECTION 13. DISPOSAL CONSIDERATIONS

000000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

Disposal methods : Observe all Federal, State, and Local Environmental regulations.

SECTION 14. TRANSPORT INFORMATION

DOT	UN/ID No.	: UN 3163
	Proper shipping name	: LIQUEFIED GAS, N.O.S. (1,1,1,2-Tetrafluoroethane, R-1234yf, Pentafluoroethane)
	Class	: 2.2
	Packing group	
	Hazard Labels	: 2.2
IATA	UN/ID No.	: UN 3163
	Description of the goods	: LIQUEFIED GAS, N.O.S. (1,1,1,2-Tetrafluoroethane, R-1234yf, Pentafluoroethane)
	Class	: 2.2
	Hazard Labels	: 2.2
	Packing instruction (cargo aircraft)	: 200
	Packing instruction (passenger aircraft)	: 200
IMDG	UN/ID No.	: UN 3163
	Description of the goods	: LIQUEFIED GAS, N.O.S. (1,1,1,2-TETRAFLUOROETHANE, R-1234yf, PENTAFLUOROETHANE)
	Class	: 2.2
	Hazard Labels	: 2.2
	EmS Number	: F-C, S-V
	Marine pollutant	: no

SECTION 15. REGULATORY INFORMATION**Inventories**

US. Toxic Substances Control Act : On TSCA Inventory

00000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

Australia. Industrial Chemical (Notification and Assessment) Act	:	On the inventory, or in compliance with the inventory
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL)	:	All components of this product are on the Canadian DSL
Japan. Kashin-Hou Law List	:	On the inventory, or in compliance with the inventory
Korea. Existing Chemicals Inventory (KECI)	:	On the inventory, or in compliance with the inventory
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	:	Not in compliance with the inventory
China. Inventory of Existing Chemical Substances	:	On the inventory, or in compliance with the inventory
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	:	On the inventory, or in compliance with the inventory
TSCA 12B	:	US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)
		2,3,3,3-Tetrafluoroprop-1-ene 754-12-1

National regulatory information

SARA 302 Components	:	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 313 Components	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.


000000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

SARA 311/312 Hazards : Sudden Release of Pressure Hazard
Acute Health Hazard

California Prop. 65 :  **WARNING:** This product can expose you to chemicals, listed below, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Dichloromethane	75-09-2
Chloromethane	74-87-3

Massachusetts RTK : Dichloromethane 75-09-2

Pennsylvania RTK : Difluoromethane 75-10-5

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous

000000023760

Version 1.0

Revision Date 10/15/2018

Print Date 05/17/2021

versions.

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group