

00000021925

Version 1.2

Revision Date 09/04/2019

Print Date 02/08/2023

SECTION 1. IDENTIFICATION

Product name : Solstice® N15 (R-515B)

Number : 00000021925

Product Use Description : Refrigerant

Manufacturer or supplier's details : Honeywell International Inc.
115 Tabor Road
Morris Plains, NJ 07950-2546

For more information call : 800-522-8001
+1-973-455-6300(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414
: **Transportation (CHEMTREC): 1-800-424-9300 or +1-703-527-3887**
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : Liquefied gas

Color : colourless

Odor : slight ether-like

Classification of the substance or mixture

Classification of the substance or mixture : Gases under pressure, Liquefied gas
Simple Asphyxiant

GHS Label elements, including precautionary statements

00000021925

Version 1.2

Revision Date 09/04/2019

Print Date 02/08/2023

Symbol(s)

:



Signal word

: Warning

Hazard statements

: Contains gas under pressure; may explode if heated.
May displace oxygen and cause rapid suffocation.

Precautionary statements

: **Prevention:**

Use personal protective equipment as required.

Storage:

Protect from sunlight. Store in a well-ventilated place.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: Mixture

Chemical name	CAS-No.	Concentration
trans-1,3,3,3-Tetrafluoroprop-1-ene	29118-24-9	91.10 %
1,1,1,2,3,3,3-Heptafluoropropane	431-89-0	8.90 %

SECTION 4. FIRST AID MEASURES

Inhalation

: Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician.

Skin contact

: Rapid evaporation of the liquid may cause frostbite. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft

000000021925

Version 1.2

Revision Date 09/04/2019

Print Date 02/08/2023

- cloth or similar covering. Call a physician if irritation develops or persists.
- Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.
- Ingestion : Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. Call a physician immediately.

Notes to physician

- Indication of immediate medical attention and special treatment needed, if necessary : Treat frost-bitten areas as needed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water mist
Dry powder
Foam
Carbon dioxide (CO₂)
- Specific hazards during firefighting : Contents under pressure.
Heating will cause pressure rise with risk of bursting
Cool closed containers exposed to fire with water spray.
Product is not combustible under normal conditions.
However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.
Do not allow run-off from fire fighting to enter drains or water courses.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Some risk may be expected of corrosive and toxic decomposition products.
Fire may cause evolution of:
Hydrogen fluoride
Carbon oxides
Carbonyl halides
Halogenated compounds
- Special protective equipment : In the event of fire and/or explosion do not breathe fumes.

00000021925

Version 1.2

Revision Date 09/04/2019

Print Date 02/08/2023

for firefighters

Wear self-contained breathing apparatus and protective suit.
No unprotected exposed skin areas.
Exposure to decomposition products may be a hazard to health.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,
protective equipment and
emergency procedures

: Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Wear personal protective equipment. Unprotected persons must be kept away.
Remove all sources of ignition.
Avoid skin contact with leaking liquid (danger of frostbite).
Ventilate the area.
After release, disperses into the air.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Avoid accumulation of vapours in low areas.
Unprotected personnel should not return until air has been tested and determined safe.

Environmental precautions

: Prevent further leakage or spillage if safe to do so.
The product evaporates readily.
Prevent spreading over a wide area (e.g. by containment or oil barriers).

Methods and materials for
containment and cleaning
up

: Do not direct water spray at the point of leakage.
Allow to evaporate.

SECTION 7. HANDLING AND STORAGE**Handling**

Precautions for safe
handling

: Handle with care.
Avoid inhalation of vapour or mist.
Do not get in eyes, on skin, or on clothing.
Wear personal protective equipment.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Follow all standard safety precautions for handling and use of compressed gas cylinders.
Use authorized cylinders only.
Protect cylinders from physical damage.

00000021925

Version 1.2

Revision Date 09/04/2019

Print Date 02/08/2023

Do not puncture or drop cylinders, expose them to open flame or excessive heat.
 Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
 Do not remove screw cap until immediately ready for use.
 Always replace cap after use.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
 Keep away from direct sunlight.
 Fire or intense heat may cause violent rupture of packages.
 Vapours may form explosive mixtures with air.
 The product is not easily combustible.

Storage

Conditions for safe storage, including any incompatibilities : Keep containers tightly closed in a cool, well-ventilated place.
 Keep away from direct sunlight.
 Protect cylinders from physical damage.
 Store away from incompatible substances.

Further information on storage conditions : Keep only in the original container at temperature not exceeding 50°C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Do not breathe vapour.
 Avoid contact with skin, eyes and clothing.
 Ensure that eyewash stations and safety showers are close to the workstation location.

Engineering measures : Local exhaust

Eye protection : Goggles

Hand protection : Protective gloves

Skin and body protection : Impervious clothing
 Wear cold insulating gloves/ face shield/ eye protection.

Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment.
 Wear a positive-pressure supplied-air respirator.

00000021925

Version 1.2

Revision Date 09/04/2019

Print Date 02/08/2023

Hygiene measures : Avoid breathing vapours, mist or gas.
Keep working clothes separately.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis
trans-1,3,3,3-Tetrafluoroprop-1-ene	29118-24-9	TWA : Time weighted average	(800 ppm)	2012	WEEL:US. OARS. WEELs Workplace Environmental Exposure Level Guide
trans-1,3,3,3-Tetrafluoroprop-1-ene	29118-24-9	TWA : Time weighted average	(800 ppm)	31.03.11	Honeywell:Limit established by Honeywell International Inc.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquefied gas

Color : colourless

Odor : slight ether-like

Odor threshold : Note: no data available

pH : Note: neutral

Melting point/range : Note: no data available

Boiling point/boiling range : Note: no data available

Flash point : Note: Not applicable

Evaporation rate : Note: Not applicable

00000021925

Version 1.2

Revision Date 09/04/2019

Print Date 02/08/2023

Lower explosion limit	: Note: no data available
Upper explosion limit	: Note: no data available
Vapor pressure	: 440 kPa at 21 °C(70 °F)
Vapor density	: Note: no data available
Density	: Note: no data available
Water solubility	: Note: no data available
Partition coefficient: n-octanol/water	: Note: no data available
Ignition temperature	: Note: not determined
Viscosity, dynamic	: Note: Not applicable
Viscosity, kinematic	: Note: Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Hazardous polymerisation does not occur.
Conditions to avoid	: Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Can form a combustible mixture with air at pressures above atmospheric pressure. Do not mix with oxygen or air above atmospheric pressure.
Incompatible materials	: Reactions with alkali metals.

00000021925

Version 1.2

Revision Date 09/04/2019

Print Date 02/08/2023

Hazardous decomposition products : Carbon oxides
Carbonyl halides
Hydrogen fluoride
Halogenated compounds

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : Note: Not applicable study technically not feasible

Acute inhalation toxicity
trans-1,3,3,3-Tetrafluoroprop-1-ene : 100000 ppm
Species: Mouse
Note: Acute (4-Hour) Inhalation Toxicity Screening Study (mouse): No lethality at >100,000 ppm.

LC50: > 207000 ppm
Exposure time: 4 h
Species: Rat

Acute dermal toxicity : Note: no data available study technically not feasible

Skin irritation
trans-1,3,3,3-Tetrafluoroprop-1-ene : Species: Rabbit
Result: No skin irritation
Method: OECD Test Guideline 404

Eye irritation : Note: no data available study technically not feasible

Sensitisation
trans-1,3,3,3-Tetrafluoroprop-1-ene : Cardiac sensitization
Species: dogs
Note: Did not cause sensitisation on laboratory animals.

Repeated dose toxicity
trans-1,3,3,3- : Species: Rat

00000021925

Version 1.2

Revision Date 09/04/2019

Print Date 02/08/2023

Tetrafluoroprop-1-ene

Application Route: Inhalation
Exposure time: (13 Weeks)
NOEL: 5000 ppm
Causes mild effects on the heart.

Genotoxicity in vitro
trans-1,3,3,3-
Tetrafluoroprop-1-ene

: Test Method: Chromosome aberration test in vitro
Cell type: Human lymphocytes
Result: negative

: Test Method: Ames test
Result: negative

Genotoxicity in vivo
trans-1,3,3,3-
Tetrafluoroprop-1-ene

: Test Method: Mutagenicity (in vivo mammalian bone-marrow
cytogenetic test, chromosomal analysis)
Species: Mouse
Cell type: Micronucleus
Application Route: Inhalation
Result: negative

Teratogenicity
trans-1,3,3,3-
Tetrafluoroprop-1-ene

: Species: Rabbit
Method: Prenatal Developmental Inhalation Toxicity Study
Note: Did not show teratogenic effects in animal experiments.

Species: Rat
Method: Prenatal Developmental Inhalation Toxicity Study
Note: Did not show teratogenic effects in animal experiments.

Further information

: Note: Excessive exposure may cause central nervous system effects including drowsiness and dizziness. Excessive exposure may also cause cardiac arrhythmia. Rapid evaporation of the liquid may cause frostbite.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity to fish

000000021925

Version 1.2

Revision Date 09/04/2019

Print Date 02/08/2023

trans-1,3,3,3-
Tetrafluoroprop-1-ene : NOEC: > 117 mg/l
Exposure time: 96 h
Species: Cyprinus carpio (Carp)

Toxicity to daphnia and other aquatic invertebrates
trans-1,3,3,3-
Tetrafluoroprop-1-ene : EC50: > 160 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)

Toxicity to algae
trans-1,3,3,3-
Tetrafluoroprop-1-ene : Growth inhibition
NOEC: > 170 mg/l
Exposure time: 72 h
Species: Algae

Biodegradability
trans-1,3,3,3-
Tetrafluoroprop-1-ene : aerobic
Result: Not readily biodegradable.

Further information on ecology**SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods : Observe all Federal, State, and Local Environmental regulations.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 3163
Proper shipping name : LIQUEFIED GAS, N.O.S.
(trans-1,3,3,3-Tetrafluoroprop-1-ene, 1,1,1,2,3,3,3-
Heptafluoropropane)
Class : 2.2
Packing group :
Hazard Labels : 2.2

IATA UN/ID No. : UN 3163
Description of the goods : LIQUEFIED GAS, N.O.S.
(trans-1,3,3,3-Tetrafluoroprop-1-ene, 1,1,1,2,3,3,3-

000000021925

Version 1.2

Revision Date 09/04/2019

Print Date 02/08/2023

		Heptafluoropropane)
Class	:	2.2
Hazard Labels	:	2.2
Packing instruction (cargo aircraft)	:	200
Packing instruction (passenger aircraft)	:	200

IMDG	UN/ID No.	:	UN 3163
	Description of the goods	:	LIQUEFIED GAS, N.O.S. (TRANS-1,3,3,3-TETRAFLUOROPROP-1-ENE, 1,1,1,2,3,3,3-HEPTAFLUOROPROPANE)
	Class	:	2.2
	Hazard Labels	:	2.2
	EmS Number	:	F-C, S-V
	Marine pollutant	:	no

SECTION 15. REGULATORY INFORMATION**Inventories**

US. Toxic Substances Control Act : On TSCA Inventory

Australia. Industrial Chemical (Notification and Assessment) Act : On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law List : Not in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI) : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act : Not in compliance with the inventory

: trans-1,3,3,3-Tetrafluoroprop-1-ene 29118-24-9

000000021925

Version 1.2

Revision Date 09/04/2019

Print Date 02/08/2023

China. Inventory of Existing Chemical Substances (IECSC) : 1,1,1,2,3,3,3-Heptafluoropropane 431-89-0
: On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand : On the inventory, or in compliance with the inventory

National regulatory information

SARA 302 Components : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards : Sudden Release of Pressure Hazard
Acute Health Hazard

California Prop. 65 : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0

000000021925

Version 1.2

Revision Date 09/04/2019

Print Date 02/08/2023

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 05/18/2017

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group